



# Mirage

OPERATORY SYSTEM



MODEL 2015



# TPC Mirage Operator System

## Model 4000 Dental Chair

### Standard Features

Three operator-programmable position, one preset exit position  
 Electronic foot switch preposition / auto return switch  
 Fuse / surge protection  
 Toe guard protection  
 Synchronized seat and toe board tilt  
 All metal construction  
 Thin back with lumbar support  
 Double articulating headrest  
 Safety shut-off plate  
 Pivoting armrest  
 Seamless asepsis upholstery  
 Input voltage (110v or 220v)- specify  
 5 year warranty

## Mirage Chair Mounted Delivery System

### Standard Features

Asepsis automatic control for three handpieces with syringe  
 Individual handpiece pressure adjustments  
 Non-retracting water coolant with on/off  
 Individual water coolant flow controls  
 Air coolant flow control  
 Handpiece tubing flush system  
 Ultra soft handpiece tubing  
 4 hole straight gray asepsis tubing with Midwest connector  
 Stainless steel tray with non-skid pad  
 Disc foot control wet/dry toggle with 7" of smooth tubing  
 Equipment utility center with asepsis housing  
 Vacuum canister with solids collector screen  
 Straight light post for unit mount dental light  
 Pre-wiring for fiber optic light source  
 Air-actuated counterbalanced arm lock

## Mirage Post Mount Utility Center

### Standard Features

Gravity drain swing away porcelain cuspidor  
 Adjustable timed bowl rinse with push-button cup filler  
 Self contained water system with city/ bottle selector  
 Water outlet with flow control  
 Air outlet with flow control  
 Vacuum canister with solids collector screen

## Assistant's Instrumentation

### Standard Features

Telescoping arm with movable assistant's instrument holder  
 One autoclavable HVE with asepsis tubing  
 One autoclavable saliva ejector with tubing

## Dental Operatory Light

**L700-1** Advance Operatory Light, 12,000 lux / 24,000 lux, 4,500° Kelvin

**L825** Lucent Operatory Light (sensor), 29,000 lux / 17,000 lux, 4,600° Kelvin

**L800** Lucent Operatory Light (no sensor), 29,000 lux / 17,000 lux, 4,600° Kelvin

	4000 (Dental Chair)	2000 (Unit w/Cuspidor)	2015 (Unit w/o Cuspidor)	L700 (Standard Operatory Light)	L825 (Sensor Operatory Light)	L800 (No Sensor Light)
Three operator-programmable position, one preset exit position	•					
Electronic foot switch preposition / auto return switch	•					
Fuse / surge protection	•					
Toe guard protection	•					
Synchronized seat and toe board tilt	•					
All metal construction	•					
Thin back with lumbar support	•					
Double articulating headrest	•					
Safety shut-off plate	•					
Pivoting armrest	•					
Seamless asepsis upholstery	•					
Input voltage (110v or 220v)- specify	•					
5 year warranty	•					
Asepsis automatic control for three handpieces with syringe		•	•			
Individual handpiece pressure adjustments		•	•			
Non-retracting water coolant with on/off		•	•			
Individual water coolant flow controls		•	•			
Air coolant flow control		•	•			
Handpiece tubing flush system		•	•			
Ultra soft handpiece tubing		•	•			
4 hole straight gray asepsis tubing with Midwest connector		•	•			
Stainless steel tray with non-skid pad		•	•			
Disc foot control wet/dry toggle with 7" of smooth tubing		•	•			
Equipment utility center with asepsis housing		•	•			
Vacuum canister with solids collector screen		•	•			
Straight light post for unit mount dental light		•	•			
Pre-wiring for fiber optic light source		•	•			
Air-actuated counterbalanced arm lock		•	•			
Gravity drain swing away porcelain cuspidor		•				
Adjustable timed bowl rinse with push-button cup filler		•				
Self contained water system with city/ bottle selector		•	•			
Water outlet with flow control		•	•			
Air outlet with flow control		•	•			
Vacuum canister with solids collector screen		•	•			
Telescoping arm with movable assistant's instrument holder		•	•			
One autoclavable HVE with asepsis tubing		•	•			
One autoclavable saliva ejector with tubing		•	•			
<b>L700-1</b> Advance Operatory Light, 12,000 lux / 24,000 lux, 4,500° Kelvin				•		
<b>L825</b> Lucent Operatory Light (sensor), 29,000 lux / 17,000 lux, 4,600° Kelvin					•	
<b>L800</b> Lucent Operatory Light (no sensor), 29,000 lux / 17,000 lux, 4,600° Kelvin						•

## Factory Options

Additional 3 way syringe  
 Additional HVE with tubing  
 Power optic system, ISO B (5-hole)  
 Power optic system, ISO C (6-pin)  
 Built-in piezo scaler with transformer  
 Super thin x-ray viewer- unit mounted  
 Standard LCD monitor bracket  
 Deluxe LCD monitor bracket  
 Mirage LCD monitor bracket  
 15" standard multi media LCD monitor  
 15" Deluxe multi media LCD monitor w/ x-ray viewer  
 Plastic utility shelf- (grey, white or beige)-post mounted  
 Touch pad-unit head mounted

## Item Number

#TPC3WAY  
 #2000HVE  
 #H7000  
 #H7660  
 #A800-1  
 #XV100/150  
 #WIC800  
 #WIC825  
 #WIC840  
 #M015  
 #MTFT15  
 #US100  
 #TP-2000

## Packing Dimensions

55 x 33 x 33	350 lbs.
50 x 5 x 22	20 lbs.
51 x 20 x 17	85 lbs.
23 x 20 x 19	36 lbs.

## Upholstery Selections:

